Rec'd PCT/PTO 15 APR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



I DANK KANDON NI DIKAN NIKA BENA BINA BINA KAND NIKA BINA BINA BINA BINA BINA BINA BINA DIKAN NIKA BINA DIKAN

(43) International Publication Date 22 July 2004 (22.07.2004)

(10) International Publication Number WO 2004/061018 A1

(51) International Patent Classification7: C09D 4/00, 5/00

Circle, Berwyn, PA 19312 (US). TRONCO, Henry, A., Jr. [US/US]; 756 Rhoads Drive, Springfield, PA 19064 (US).

(21) International Application Number:

PCT/US2003/041625

(74) Agent: DESMUKH, Sudhir, G.; E.I. DUPONT DE NEMOURS AND COMPANY, LEGAL PATENT RECORDS CENTER, 4417 Lancaster Pike, Wilmington, DE 19805 (US).

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,

IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(22) International Filing Date:

30 December 2003 (30.12.2003)

(81) Designated States (national): CA, MX, US.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/433,129

31 December 2002 (31.12.2002)

(71) Applicant (for all designated States except US): E.I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).

Published:

with international search report

before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(72) Inventors; and

(75) Inventors/Applicants (for US only): MA, Sheau-Hwa [US/US]; 1235 Twaddell Drive, West Chester, PA 19382 (US). MATTHEWS, James, F. [US/US]; 11 Lakeview For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROCESS FOR PRODUCING MULTI-COAT SYSTEM ON SUBSTRATE

(57) Abstract: The present invention relates to a process for producing a multi-coat system on various substrates, particularly automotive bodies. A crosslinkable component of the composition includes an acid functional acrylic copolymer polymerized from a monomer mixture comprising 2 percent to 12 percent of one or more carboxylic acid group containing monomers, percentages based on total weight of the acid functional acrylic copolymer, and 0.2 percent to 2 percent of amorphous silica, percentages based on total weight of the crosslinkable component. The crosslinking component can includes polyisocyanates, melamines, or a combination thereof.